






### ENERGY-SAVING TOWER UPS



### The energy-saving UPS to save up to 93% of power consumption

Designed for home, SOHO office and office applications, the UT Series adopts line-interactive topology with Automatic Voltage Regulation (AVR) function to offer stabilized AC power output. The patented GreenPower UPS™ Bypass design achieves ultra-low power consumption to reduce energy costs. The LED indicator shows the utility, battery and operating status of the UPS. Other features include overload protection, EMI filter and configurable alarm to safeguard your devices.

#### APPLICATION




- Home
- Office
- SOHO Office

#### SERIES FEATURES

- Line-interactive UPS Topology
- Automatic Voltage Regulation (AVR)
- LED Status Indicator
- High-Speed Ethernet Data Transmission
- Configurable Alarm
- Energy Saving Technology
- Generator Compatible
- Phone/Fax/Modem/DSL/Network Protection
- EMI and RFI Filtration
- PowerPanel® Management Software

#### PRODUCT CALLOUTS

1. Power On/Off Switch
2. LED Status Indicators
3. USB Port
4. Battery Backup & Surge Protected Outlets
5. Input Circuit Breaker
6. Communication Protection Ports RJ11/RJ45
7. AC Input Power Cord



UT1050EG



## TECHNICAL SPECIFICATIONS

<b>Model Name</b>	<b>UT1050EG</b>
<b>General</b>	
UPS Topology	Line-interactive
Energy Saving Technology	GreenPower UPS™ Bypass Technology
<b>Input</b>	
Generator Compatibility	Yes
Nominal Input Voltage (Vac)	230 ± 10%
Input Voltage Range (Vac)	165 - 290
Input Frequency (Hz)	50 ± 5, 60 ± 5
Input Frequency Detection	Auto-sensing
Rated Input Current (A)	4.56
Input Connector Type	Schuko
<b>Output</b>	
Capacity (VA)	1050
Capacity (Watts)	630
On Battery Waveform	Simulated Sine Wave
On Battery Voltage(s) (Vac)	230 ± 10%
On Battery Frequency (Hz)	50 ± 1%, 60 ± 1%
Automatic Voltage Regulation (AVR)	Single Boost, Single Buck
Overload Protection	Circuit Breaker
Outlet(s) - Total	4
Outlet Type	Schuko x 4 or FR x 4
Outlet(s) - Battery & Surge Protected	4
Typical Transfer Time (ms)	4
<b>Battery</b>	
Runtime at 60W (min)	65
Runtime at 90W (min)	43
Runtime at 200W (min)	14
Typical Recharge Time (Hours)	6
User-replaceable	No
Battery Type	Sealed Lead-acid
<b>Surge Protection &amp; Filtering</b>	
Surge Suppression (Joules)	150
EMI/RFI Filtration	Yes
Phone/Network Protection RJ11/RJ45 (Combo)	1-in, 1-out
<b>Management &amp; Communications</b>	
LED Indicators	Power On, Line Mode, Battery Mode, Bypass Mode, Low Battery, Overload, UPS Fault
HID Compliant USB Port(s)	1
Audible Alarms	Battery Mode, Low Battery, Overload, UPS Fault
Ethernet Data Transmission Speed	Up to 1Gb
Power Management Software	PowerPanel® Personal Edition
<b>Physical</b>	
Form Factor	Tower
<b>Physical Size - UPS Module</b>	
Dimensions (WxHxD) (mm.)	95 x 220 x 307
Weight (kg.)	6.9
<b>Environmental</b>	
Operating Temperature (°C)	0 - 40
Operating Relative Humidity (Non-condensing) (%)	0 - 90
Online Thermal Dissipation (BTU/hr)	8
<b>Certifications</b>	
Certifications*	CE, EAC
RoHS	Yes

\*Certifications may vary according to different regions. Visit [www.cyberpower.com](http://www.cyberpower.com) for more information.  
#All specifications are subject to change without notice.